



LEICA C-LUX 2

Exquisite, effortless, exclusive



Photography has never been so enjoyable. If you value style but not weight when you're out looking for great images, you'll love the ultra compact LEICA C-LUX 2! Sporting a classic black or silver metal body and measuring just 3 1/2 x 2 in, it fits into even the smallest pocket. The elegant exterior design is unmistakably Leica and is matched by an immaculate standard of optics and digital technology inside: The high-speed wide-angle 28 mm zoom lens takes stunning, space-grabbing shots. And its 7.2 megapixel resolution, fast image signal processor, precise exposure control and optical image stabilization will give you outstanding, effortless results – from imposing portraits to fascinating travel impressions.

Illustrations in original size



Leather case Exclusive yet practical: the camera case high-quality leather. Choice of three colors. Black **Order no. 18 677**, red **Order no. 18 678**, brown **Order no. 18 679**

Wrist carrying strap The perfect and color-coordinated addition to the leather case. Black **Order no. 18 684**, red **Order no. 18 685**, brown **Order no. 18 686**



Neoprene case The smart but casual modern camera case in black with practical belt loop. **Order no. 18 680**



Carrying strap The neckstrap features a small SD card pocket accommodating two extra memory cards. Black **Order no. 18 681**, red **Order no. 18 682**, brown **Order no. 18 683**

The optical image stabilizer and the intelligent exposure control prevent camera shake and ensure optimum definition. The 7.2 megapixel CCD sensor enables superlative prints up to poster size. The focal length range of the Leica wide-angle zoom lens is equivalent to 28 – 100 mm in 35 mm format. The super flat metal body is available in either black or silver. The extra large 2.5" display, the image stabilization and short shutter delay of the LEICA C-LUX 2 all guarantee carefree photography with high-quality results.

Technical Data

Camera	LEICA C-LUX 2
Image type/format	1/2.5" CCD sensor with 7.38 million pixels (7.2 m pixels effective in 4:3 format).
Resolution	In 4:3 format either 3,072 x 2,304 pixels, 2,560 x 1,920 pixels, 2,048 x 1,536 pixels, 1,600 x 1,200 pixels, 1,280 x 960 pixels or 640 x 480 pixels. In Leica 3:2 format either 3,072 x 2,048 pixels or 2,048 x 1,360 pixels. In 16:9 format either 3,072 x 1,728 pixels or 1,920 x 1,080 pixels (corresponds to HDTV standard).
Video sequences	In 16:9 format with 848 x 480 pixels, in 4:3 format with 640 x 480 pixels or in 4:3 format with 320 x 240 pixels at either 30 fps or 10 fps, duration of recording limited by the capacity of the memory card. Recordings with sound. (Duration of recordings for UK/EU/ES-SCAN versions max. 15 min)
Data recording	File formats: Still pictures JPEG (Fine/Standard), Video QuickTime Motion JPEG.
Storage media	SDHC memory card, SD memory card and MultiMedia card (a 64 MB SD card is supplied with the camera)
Film speed setting	Either automatic, Intelligent ISO or manual ISO 100, ISO 200, 400, 800 or ISO 1250 (in high-sensitivity mode: 3200)
White balance	Either automatic, for daylight, overcast sky, halogen light, manual setting, fine adjustment of white balance in a range of -1500 to +1500 K in 150 K steps (not available for automatic setting).
Lens	LEICA DC VARIO-ELMARIT f/2.8 – 5.6/4.6 – 16.4 mm ASPH. (corresponds to 28 – 100 mm for 35 mm photography in 4:3 picture format) 3.6 x optical zoom. Change of focal length by conveniently located zoom lever. 7 elements in 6 groups (5 aspherical lens elements/6 aspherical surfaces) with optical image stabilization.
Optical image stabilizer	2 modes: either for exposure only or for monitor image and exposure.
Focus range	Normal: 50 cm (20 in) – infinity, Macro/Simple/Motion Picture: wide-angle 5 cm (2 in)/telephoto 30 cm (12 in) – infinity.
Focusing	Autofocus, either normal or macro. Autofocus mode/measurement range either 5 fields (full image area), faster autofocus with 3 fields (across the center) or with 1 central field, 1 field or spot.
Exposure	Exposure modes Either simple mode, normal or macro. Exposure measurement multi-field metering, Exposure bracketing ±2 EV in 1/2 EV steps.
Series exposures	Either 3 fps or 2 fps at full resolution, max. 7 pictures with JPEG standard, max. 5 pictures with JPEG fine or only limited by memory card capacity in "Unlimited" mode.
Shutter speed range	In fully automatic mode: 8 – 1/2000 s. Starry sky mode: 15, 30, 60 s. Video mode: 1/30 s – 1/6400 s.
Flash	Flash modes either automatic flash on with or without pre-flash (to reduce red-eye), manual flash on (fill-in flash), SLOW for slower shutter speeds (with pre-flash), flash off. Flash range (ISO set at Auto): 0.6 – 5.0 m (wide-angle), 0.3 – 2.0 m (telephoto), in high sensitivity mode: 0.8 – 5.7 m (wide-angle), 0.8 – 2.8 m (telephoto).
Scene modes	Portrait, soft skin, landscape, sport, night portrait, night landscape, starry sky, fireworks, food, party, candlelight, baby 1, baby 2, pets, sunset, high sensitivity, beach, snow, aerial, underwater.
Function key	For direct control of: image stabilizer, bracketing speed, white balance, ISO setting, picture size, compression.
Toning effects	Natural, standard, lively, blueish, reddish, black-and-white or sepia.
LCD monitor	2.5" polycrystalline TFT color display with 207,000 pixels. Field of view: almost 100% Power LCD mode, wide-angle viewing mode.
Self timer	Either 2 or 10 s countdown.
Live histogram	yes
Power supply	Lithium-ion battery (LEICA BP-DC6), 3.6 V, 1000 mAH or optional mains unit (LEICA ACA-DC4).
Ports	USB 2.0 (Full speed), DC in (power supply) and AV out.
Printer compatibility	PictBridge
Battery capacity (approx.)	300 frames (CIPA standard)
Dimensions (W x H x D)	approx. 94.9 x 51.9 x 22 mm (3.7 x 2 x 9 inches)
Weight	approx. 132 g (4.6 oz) without battery and memory card; approx. 154 g (5.4 oz) with battery and SD memory card.
Scope of delivery	Battery charger, battery, 64 MB SD memory card, AV cable, USB cable, AC cable, wrist strap, CD-ROM with software (Adobe Photoshop Elements 3/4/5, QuickTime Movieplayer).
Accessories	
Charger/mains unit	(replacement) ACA-DC4 with mains cable
Lithium-ion battery	(replacement) LEICA BP-DC6
Digital adapter	Digital adapter 2 for Leica TeleviD Order no. 42 303

Leica is a trademark of the Leica Camera Group / "Leica" and product names – ® Registered trademarks / © 2007 Leica Camera AG / All rights to change construction, design and range reserved / Concept and Design: Heine/Lenz/Zizka, Frankfurt am Main / Image indication: Product photography Tom Vack, Alexander Göhr / Photostory: Frank Rothe / Brochure order number: German 91332, English 91333, US-English 91334, French 91335, Italian 91336, Dutch 91337, Japanese 91338, Danish 91339, Norwegian 91340, Spanish 91341, Portuguese 91342 / 02/07/FFVX/D



LEICA C-LUX 2

